

SB-200 Liquid Membrane Brush Grade

SBH SEAL Liquid Membrane is a single component liquid applied waterproofing system combining high-quality bitumen with various polymers that form a high-performance elastomeric waterproof membrane. SBH Seal Liquid membrane is designed for re-roof your complete wear and tear roof creating a new membrane for a long-lasting time, and for multiple surfaces concrete, foundation. Ideal for sealing cracks, joints and flashings. SBH SEAL Liquid Membrane contains no solvents or VOC's. and will not damage polyurethane or polystyrene insulation materials.

Properties:

- Applied at any thickness in a single pass.
- Brush or Roller or broom applied.
- Strong, seamless and fully adherent to the surface with minimal preparation.
- Effective for waterproofing and protection against corrosion.
- High elasticity (up to 1300%!).
- UV- and acid-resistant.
- Resists hydrostatic head pressure.
- Applied easily around obstacles.
- Environmentally friendly and contains no VOC's or other toxics.

Warrenty:

SBH Seal liquid membrane is a protective membrane of umparalleled quality and durability. It has a 10-year warranty and tested to independent ASTM international standards.



SPRAYGRADE
AND BRUSHGRADE
ENVIRONMENTALLY
FRIENDLY PRODUCTS

SBH SEAL
REVOLUTIONARY
MEMBRANE

Get In Touch With Us

SBH SEAL

525 South Ave
Plainfield, NJ, 07060

Phone : (908) 845-9110

Email : info@sbhseal.com

Web : www.sbhseal.com



www.sbhseal.com

SB-100 Liquid Membrane Spray Grade



Guarantees the best and the most cost effective benefits compared to conventional membrane systems, our mission is to provide the best quality membrane at low cost.

Seamless Elastomeric Membrane

SBH Seal Spray is an eco-friendly, elastomeric water-based protective membrane that combines a unique bitumen emulsion with certain polymers to create a high performance, cost-efficient liquid applied roof waterproofing membrane. Spray applied in combination with an inorganic rapid set accelerator, SBH Seal Spray instantly forms a rubber-like, fully adhered waterproof membrane for new and restoration roofing projects.

Spray Rig



HVLP 2000 Pump System

SBH Seal Spray is applied using a dual diaphragm pump system that is easy to use delivering up to 2000 ft per hour with a 2 man crew and can be fitted with up to 1000' of hose. Also available as a skid mount pallet for a truck cab or pickup installation.

Spray Properties

- Waterproof - low vapor permeability.
- Excellent adhesion to most substrates so water will not run beneath the membrane.
- No VOC's, No solvents & No harmful odors.
- Resists cracking and chipping.
- Freeze/thaw stable - stored at any temperature.
- Highly Flexible.

Suitable Applications Include:

- Commercial Flat and Low Slope.
- Polyurethane foam & foam boards.
- Modified-Bitumen Membranes
- Metal Factory and Warehousing.
- EPDM-TPO Roofs (w/ Primer).
- Concrete & Plywood.



Covering Area

80 Mills Dry.....13 Sq ft per gallon.
40 Mills Dry.....26 Sq ft per gallon.

